



LYON STATION, PA 19536 • Phone: 610-682-6361 • Fax: 610-682-4781
Order Department Hotline: 610-682-4231
www.dekabatteries.com

MARINE MASTER®

GROUP NO.	PART NO.	CCA	REF. MCA	20 HR CAP	MINS @ 23 A	MINS @ 25 A	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
								in	mm	in	mm	in	mm			
12-VOLT MARINE / RV STARTING CALCIUM MAINTENANCE-FREE																
24	24M7	800	1000	—	—	130	46	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
	24M6	650	800	—	—	115	40	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
	24M5	550	675	—	—	90	37	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
	24M4	460	565	—	—	70	36	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	17,22,U
27	27M6	840	1050	—	—	182	53	12-1/2	318	6-3/4	171	9-3/8	238	1.0	12	17,U
12-VOLT MARINE / RV DUAL PURPOSE STARTING / CYCLE SERVICE																
24	DP24	550	675	65	140	120	44	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	12,17,44,U
27	DP27	650	800	80	175	150	51	12-1/2	318	6-3/4	171	9-3/8	238	1.0	12	12,17,44,U
31	DP31DT	700	860	100	205	185	57	13	330	6-3/4	171	9-1/2	241	1.5	12	17,21,22,44,A
12-VOLT MARINE / RV DEEP CYCLE SERVICE																
24	DC24	500	615	75	150	130	45.5	10-3/4	273	6-3/4	171	9-3/8	238	1.0	12	11,17,35,44,U
27	DC27	575	705	90	200	175	53.5	12-1/2	318	6-3/4	171	9-3/8	238	1.0	12	11,17,35,44,U
31	DC31DT	650	800	105	225	190	60	13	330	6-3/4	171	9-1/2	241	1.5	12	11,17,21,22,35,44,A

Note: "DC" (deep cycle) part numbers include double insulated glass mat separators.

GROUP NO.	PART NO.	CCA	REF. MCA	8 HR CAP	6 HR CAP	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES	
							in	mm	in	mm	in	mm				
8-VOLT MARINE AND INDUSTRIAL																
983	819	510	625	167	158	119		24-1/2	622	7-1/2	191	10-1/2	267	3.0	6	11,17,20,25,35,T
984	821	530	650	187	177	135		27-1/2	699	7-1/2	191	10-1/2	267	3.0	6	11,17,20,25,35,T
985	825	730	900	224	212	160		26-7/8	683	8-1/2	216	11-3/4	298	4.0	6	11,17,20,25,35,F

Deka INTIMIDATOR®

**AGM VALVE-REGULATED
ABSORBED GLASS MAT TECHNOLOGY**

GROUP NO.	PART NO.	CCA	REF. MCA	R.C.	MINS @ 25 A	20 HR CAP	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
								in	mm	in	mm	in	mm			
U1	8AU1	200	240	45	54	32	23	7-3/4	197	5-1/8	130	7-1/4	184	0.5	12	2,38,39,44,Y
	8AU1H	200	240	45	54	32	23	8-5/16	211	5-1/8	130	7-1/4	184	0.5	12	2,17,38,39,44,Y
22NF	8A22NF	350	420	85	95	55	37	9	228	5-1/2	140	9-1/4	235	0.5	12	2,38,39,44,G
24M	8A24M	525	800	135	145	79	52	10-7/8	276	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,U
	8A24	525	800	135	145	79	52	10-7/8	276	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,G
24	8A24NH	525	800	135	145	79	52	10-1/4	260	6-3/4	171	9-3/8	238	1.0	12	2,38,39,44,G
	8A27M	580	900	175	185	92	61.5	12-3/4	324	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,U
27	8A27	580	900	175	185	92	61.5	12-3/4	324	6-3/4	171	9-3/8	238	1.0	12	2,17,38,39,44,G
31M	8A31DTM	800	1000	200	210	105	67.5	12-15/16	329	6-3/4	171	9-3/8	238	1.5	12	2,16,17,38,39,44,A
4D	8A4D	1110	1420	380	413	198	133.5	20-3/4	527	8-1/2	216	10	254	3.0	12	2,17,44
8D	8A8D	1450	1800	480	517	245	163	20-3/4	527	11	279	10	254	4.0	12	2,17,44
GC2 (ev)	8AGC2	680	900	380	409	190	68	10-1/4	260	7-1/8	181	10-7/8	276	1.5	12	2,44,U

Deka DOMINATOR®

**GEL VALVE-REGULATED
GELLED ELECTROLYTE TECHNOLOGY**

GROUP NO.	PART NO.	CCA	REF. MCA	R.C.	MINS @ 25 A	20 HR CAP	WEIGHT (lb)	LENGTH		WIDTH		HEIGHT		Core Value	WARRANTY FREE MO.	FOOTNOTES
								in	mm	in	mm	in	mm			
U1	8GU1	200	290	44	47	31.6	23.5	7-3/4	197	5-1/8	130	7-1/4	184	0.5	12	4,38,39,44,Y
	8GU1H	200	290	44	47	31.6	23.5	8-5/16	211	5-1/8	130	7-1/4	184	0.5	12	4,17,38,39,44,Y
22NF	8G22NF	210	300	77	82	51	37.5	9	228	5-1/2	140	9-1/4	235	0.5	12	4,38,39,44,G
24M	8G24M	410	575	132	140	73.6	51.5	10-7/8	276	6-3/4	171	9-3/8	238	1.0	12	4,17,38,39,44,U
	8G24	335	470	132	140	73.6	51.5	10-7/8	276	6-3/4	171	9-3/8	238	1.0	12	4,17,38,39,44,G
24	8G24NH	335	470	132	140	73.6	51.5	10-1/4	260	6-3/4	171	9-3/8	238	1.0	12	4,38,39,44,G
	8G24SS	335	470	132	140	73.6	51.5	10-1/4	260	6-3/4	171	8-1/4	210	1.0	12	4,38,39,44,C
27M	8G27M	505	700	160	170	88	62	12-3/4	324	6-3/4	171	9-3/8	238	1.0	12	4,17,38,39,44,U
27	8G27	400	550	160	170	88	62	12-3/4	324	6-3/4	171	9-3/8	238	1.0	12	4,17,38,39,44,G
	8G27/T876	400	550	160	170	88	62	12-3/4	324	6-3/4	171	9-1/4	235	1.0	12	4,17,38,39,44,B
30H	8G30H	450	640	180	190	97.6	68.5	12-15/16	329	6-3/4	171	9-3/4	248	1.5	12	4,17,38,39,44,B
31M	8G31DTM	550	780	180	190	97.6	68.5	12-15/16	329	6-3/4	171	9-3/8	238	1.5	12	4,16,17,38,39,44,A
31	8G31	450	640	180	190	97.6	68.5	12-15/16	329	6-3/4	171	9-3/8	238	1.5	12	4,17,38,39,44,X
34R	8G34R	300	420	90	96	60	38.5	10-3/16	259	6-5/8	168	7	178	1.0	12	4,38,39,44,C
—	8G40C	225	325	59	63	40	31.5	7-3/4	197	6-5/8	168	6-7/8	175	0.5	12	4,38,39,44,C
4D	8G4D	970	1245	375	395	183	127.5	20-3/4	527	8-1/2	216	10	254	3.0	12	4,17,38,39,44
8D	8G8D	1150	1470	475	500	225	157	20-3/4	527	11	279	10	254	4.0	12	4,17,38,39,44
GC2 (ev)	8GGC2	585	850	345	375	180	69	10-1/4	260	7-1/8	181	10-7/8	276	1.5	12	4,38,39,44,U
	8GBVGC	400	575	250	270	140	70	10-1/4	260	7-1/8	181	10-7/8	276	1.5	12	4,44,U
5SHP	8G5SHP	450	640	200	218	115	84.5	13-5/8	345	6-3/4	172	11	280	1.5	12	4,17,44
	8G5SHP876	450	640	200	218	115	84.5	13-5/8	345	6-3/4	172	11-7/16	290	1.5	12	4,17,44,B

- Batteries are maintenance-free calcium grids, except where noted
- Batteries manufactured in polypropylene cases & covers
- Batteries manufactured in black cases & covers, except where noted
- SAE automotive posts used, unless noted
- Warranty is suggested months
- Weights are approximates
- MCA and CA ratings @ 32°F are approximations for comparison only
- Ratings except CCA and RC, are "nominal"
- CCA and RC ratings conform to B.C.I. specifications
- CCA on 8 Volt Marine & Industrial Types is for reference only

MEMBERS OF:



AMERICAN BOAT & YACHT COUNCIL

NATIONAL MARINE MFG ASSOCIATION



E.P.M. Form No. 0194 © 2019 Rev 10/24/19 by EPM, Printed in U.S.A.

No Part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.



- A. Flush Combination terminal w/ 5/16" Stud and SAE post, Hex nuts included
- B. Flag Terminal w/ 3/8" diameter hole (T876)
- C. 1/4" 20 Copper insert terminal
- F. Double Wide L Terminal w/ two 3/8" holes (T230)
- G. Offset post w/ horizontal hole, stainless steel 5/16" bolt and hex nut (T881)
- T. Heavy Duty L terminal w/ 3/8" diameter hole (T975)
- U. Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs and wing nuts
- X. 3/8"-16 stainless steel stud posts
- Y. Small L terminal with round hole (T873)

FOOTNOTES

- Black cover / Gray case
- Gray cover / Gray case
- Low maintenance-low antimony grids
- Hybrid construction
- Dual terminal universal design
- Includes handle
- Hard rubber, multi-cell cover construction
- Anchor locked elements
- Flush manifold vented cover
- With individual vent caps
- Deduct 15% from CCA and CA rating to allow for double insulation (glass mat)
- "Non-spillable" defined by DOT (Department of Transportation) definitions
- "Non-spillable" defined by ICAO (International Civil Aviation Organization) and IATA (International Air Transport Association) definitions
- Free Replacement Warranty is 3 months in full electric vehicle use

PROPOSITION 65 WARNING: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. **WASH HANDS AFTER HANDLING.**



BayWa r.e. Solar Systems Inc.
4703 101 Street NW, T6E 0G6
Edmonton, AB
Tel: +1 844 851 2390
solar@baywa-re.ca