

# **FILTER GRILLE PANEL**

*								
	WIRPOWERS	-	NUMBER	-	100000000	-	-	
	5005546	NUMBER	Abrevent	SAT NO	100000000	9555820	10000338	
	- KARANANAN	STREEM	WEITERS AND	15550082	<b>ENVIRODE</b>	<b>Uturbinisties</b>	Patricipan	
	201001030	120203-006	SCOOLAND	SARATS	<b>SCOTOCOM</b>	10000000	ACCOUNTS OF	
	<b>DESCRIPTION</b>	<b>BARROOM</b>	<b>WERENE</b>	10000300	10101000	1000000	100000000	
	and other states	10000008	10000000	antessage.	PROSTOR	<b>DARAGE</b>	10055346	100
•	Long Colors	mount	TERMINER.	\$500000m	101000066	Voluments	STATES IN	10
	HOTINGS .	DEST(44)	DODDOD	HIGHNORY	REFERENCE	5555588	WATER AND	
	SCHOOL SHOW	70001930	10050334	MODO/H	551088B	ADDISON	2012/12/202	
					inunana:			
	<b>NUCLEOR</b>	1000000	<b>WINGSOM</b>	HINNIGHTER	NAMES OF TAXABLE	6000000	Included.	
	And in case of the local division of the loc	100000000	distances.	HARRING.	manual and	100000000	and the second s	

## APPLICATION


Filter Grille Panels add valuable ventilation to a rack for either inlet or exhaust air. Used alone, filter grille panels allow adequate air flow on natural convection applications or in conjunction with an air moving device to provide filtered air intake.


### **FEATURES**

- Permanent, Washable Aluminum Filter
  19-inch Rack Mountable
- Brushed Aluminum or Stainless Steel Grilles .

## Performance Data Filter Grille Panel

CATALOG NUMBERS					
Stainless Steel	35G19	-	7G19	875G19	105G19
Aluminum	35H19	525H19	7H19	875H19	105H19
UNIT CONSTRUCTION					·
Height PMax (in./mm)	3.5/89	5.25/133	7.00/178	8.75/222	10.50/267
Width (in./mm)	19/483	19/483	19/483	19/483	19/483
Weight (lb./kg)	2/1.0	3/1.4	5/2.2	5/2.2	5/2.2





1.05 [27]

.32 [8]


MAX


# ンと nvent|hoffman

# LOUVER PLATE KITS



Designed to provide ventilation in enclosures where excessive internal heat or excessive moisture is a problem. Although louvers cannot keep all moisture out of an enclosure, gasketing or sealing the perimeter of the louver plate reduces problems associated with moisture intrusion. These kits may be easily installed in the field by making a cutout of the proper size and attaching the louver plate in place. Louver plates are made from 14 gauge steel with an ANSI 61 gray polyester powder finish over pretreated surfaces or 316 stainless steel. Hardware is furnished for mounting. Custom sizes, materials, finishes, etc., can be provided on special order.





## Design Data Louver Plate Kits

	Dimensions					Cutout	Cutout
	AxB	Number	Thickness	Length L	Opening Area	Size, F	Size, G
CATALOG NUMBERS	in./mm	of Louvers	in./mm	in./mm	in. <sup>2</sup> /cm <sup>2</sup>	in./mm	in./mm
AVK23	3.25 x 3.25/83 x 83	3	0.19/5	2.00/51	.86/5.54	2.00/51	1.75/44
AVK23SS6	3.25 x 3.25/83 x 83	3	0.19/5	2.00/51	.86/5.54	2.00/51	1.75/44
AVK33	3.88 x 4.50/98 x 114	3	0.25/6	3.00/76	1.32/8.52	2.62/67	3.00/76
AVK33SS6	3.88 x 4.50/98 x 114	3	0.25/6	3.00/76	1.32/8.52	2.62/67	3.00/76
AVK34	4.75 x 4.50/121 x 114	4	0.25/6	3.00/76	1.76/11.35	3.50/89	3.00/76
AVK34SS6	4.75 x 4.50/121 x 114	4	0.25/6	3.00/76	1.76/11.35	3.50/89	3.00/76
AVK43	4.50 x 5.50/114 x 140	3	0.25/6	4.00/102	1.88/12.10	3.25/83	4.00/102
AVK43SS6	4.50 x 5.50/114 x 140	3	0.25/6	4.00/102	1.88/12.10	3.25/83	4.00/102
AVK44	5.62 x 5.50/143 x 140	4	0.25/6	4.00/102	2.50/16.13	4.38/111	4.00/102
AVK44SS6	5.62 x 5.50/143 x 140	4	0.25/6	4.00/102	2.50/16.13	4.38/111	4.00/102
AVK64	5.62 x 7.50/143 x 191	4	0.31/8	6.00/152	5.21/33.61	4.38/111	6.00/152
AVK64SS6	5.62 x 7.50/143 x 191	4	0.31/8	6.00/152	5.21/33.61	4.38/111	6.00/152
AVK66	7.88 x 7.50/200 x 191	6	0.31/8	6.00/152	7.82/50.45	6.62/168	6.00/152
AVK66SS6	7.88 x 7.50/200 x 191	6	0.31/8	6.00/152	7.82/50.45	6.62/168	6.00/152
AVK84	5.81 x 9.50/148 x 241	4	0.31/8	8.00/203	8.08/52.12	4.56/116	8.00/203
AVK84SS6	5.81 x 9.50/148 x 241	4	0.31/8	8.00/203	8.08/52.12	4.56/116	8.00/203
AVK86	8.19 x 9.50/208 x 241	6	0.31/8	8.00/203	12.11/78.13	6.94/176	8.00/203
AVK86SS6	8.19 x 9.50/208 x 241	6	0.31/8	8.00/203	12.11/78.13	6.94/176	8.00/203
AVK88	10.56 x 9.50/268 x 241	8	0.31/8	8.00/203	16.15/104.19	9.31/236	8.00/203
AVK88SS6	10.56 x 9.50/268 x 241	8	0.31/8	8.00/203	16.15/104.19	9.31/236	8.00/203
AVK812	15.31 x 9.50/389 x 241	12	0.31/8	8.00/203	24.22/156.26	14.06/357	8.00/203
AVK812SS6	15.31 x 9.50/389 x 241	12	0.31/8	8.00/203	24.22/156.26	14.06/357	8.00/203
Atto:2000	10.01 x 9.00/309 x 241	12	0.01/0	0.00/200	27.22/130.20	14.00/337	0.00/200

Catalog numbers ending in SS6 indicates 316L stainless steel



#### **Filter Media**

Filter media Filter media is composed of layers of slit and expanded aluminum providing hundreds of adhesive coated baffle surfaces for trapping impurities. Impurities are held throughout the depth of the filter. Washing with warm water will keep the filter clean. To achieve best results, Filter Adhesive is recommended.

	Dimensions H x W	Use with	Use with Stainless Steel
CATALOG NUMBERS	(in./mm)	Steel Louver	Louver
AFLT33	3.22x 3.25/82 x 83	AVK33	AVK33SS6
AFLT34	4.09 x 3.25/104 x 83	AVK34	AVK34SS6
AFLT43	3.84 x 4.25/98 x 108	AVK43	AVK43SS6
AFLT44	4.97 x 4.25/126 x 108	AVK44	AVK44SS6
AFLT64	4.45 x 6.25/113 x 159	AVK64	AVK64SS6
AFLT66	6.72 x 6.25/171 x 159	AVK66	AVK66SS6
AFLT84	4.64 x 8.25/118 x 210	AVK84	AVK84SS6
AFLT86	7.02 x 8.25/178 x 210	AVK86	AVK86SS6
AFLT88	9.39 x 8.25/239 x 210	AVK88	AVK88SS6
AFLT812	14.14 x 8.25/359 x 210	AVK812	AVK812SS6



#### Design

Designed for use with Louver Plate Kit. Mounting holes on filter bracket align with louver mounting holes. Hardware supplied with louvers also secures filter brackets in place. Aluminum air filters provide good arrestment of airborne dust and dirt.

#### FRESH AIR ENCLOSURE COOLING ACCESSORIES

# nventihoffman

# VENT KIT



Includes a stylized louvered cover and filter package. Use as an air inlet when a cooling fan is mounted in an enclosure or use two vent kits to allow passive airflow. Mounting hardware included. Vent Kit requires cutout shown in diagram. Available in gray (RAL 7042) or black.

CATALOG NUMBERS	XPV32	PPV32B
UNIT CONSTRUCTION		
Dimension H x W x D (in./mm)	11.81 x 7.88 x 1.03 300 x 200 x 26	11.81 x 7.88 x 1.03 300 x 200 x 26
Color	Gray	Black
4X Ø.110 3 mm 7.31 186 mm 10.94 278 mm 6.50 165 mm Cutout Dimensions		7.87 8779415

## VENTILATOR



Designed to fit most metallic and non-metallic enclosures. Proper installation will provide rainproof ventilation but will not meet Type 4 or 12 requirements. Kit includes mounting hardware, and instructions.

Supplied screws are 13-mm (.515-inch) long. Some applications may require longer screws.

CATALOG NUMBERS		
	ANMV6	ANMV3
DESIGN DATA		
Description	Large nonmetallic vent	Small nonmetallic vent
¢1.120 28 mm .80 REF 20 mm .40 REF 10 mm \$.160 4 mm .70 REF 18 mm	R.99 REF 25 mm Vo. 0 1.61 41 mm BOLT CIRCLE 1.67 REF 42 mm VENTILATOR OUTLINE	Ø.75 19 mm .59 REF .59 REF .59 REF .42 .11 mm R.08 2 mm VENTILATOR OUTLINE
		Small ventilator
Large Ver	ntilator	87541390

# FILTER ADHESIVE



Designed to maximize the efficiency of all expanded aluminum air filters. Use of Filter Adhesive doubles the dust-retention capacity of the filter. Adhesive contains a low-viscosity water-soluble oil which absorbs dirt particles trapped on the surface of the filter. Through the circulation of the oil, a renewed impurity-absorbing surface is constantly established. Washing with water will remove dust, dirt and other impurities. Once the filter is dry, recoat with adhesive.

CATALUG NUMBERS	
	AFLTAD
DESIGN DATA	
Description	Spray Adhesive



#### BayWa r.e. Solar Systems Inc.

4703-101 Street NW, T6E 5C6 Edmonton, AB Tel: +1 844 851 2390 solardistribution@baywa-re.ca